According to regulation (EC) No. 1907/2006 (REACH)



#### 26100 XSL Bismuth Vanadate Yellow

Page 1

Revised edition: 27.10.2021 Version: 5.0 Printed: 18.02.2022

# 1. Identification of the Substance/Mixture and of the Company/Undertaking

1. 1. Product Identifier

Product Name: XSL Bismuth Vanadate Yellow

Article No.: 26100

UFI: -

1. 2. Relevant identified Uses of the Substance or Mixture and Uses advised against

Identified uses:

Coloring agent for dye and varnish industry

Uses advised against:

1. 3. Details of the Supplier of the Safety Data Sheet (Producer/Importer)

Company: Kremer Pigmente GmbH & Co. KG

Address: Hauptstr. 41-47, 88317 Aichstetten, Germany

Tel./Fax.: Tel +49 7565 914480, Fax +49 7565 1606

Internet: www.kremer-pigmente.com

EMail: info@kremer-pigmente.com

Importer: --

1. 4. Emergency No.

Emergency No.: +49 7565 914480 (Mon-Fri 8:00 - 17:00)

1. 4. 2 Poison Center:

#### 2. Hazards Identification

#### 2. 1. Classification of the Substance or Mixture

Classification according to Regulation (EC) No. 1272/2008 (CLP/GHS)

This product does not require classification and labelling as

hazardous according to CLP/GHS.

Possible Environmental Effects:

#### 2. 2. Label Elements

Classification according to Regulation (EC) No. 1272/2008 (CLP/GHS)

No classification required according to the CLP/GHS guidelines.

Hazard designation:

Not applicable.

Signal word:

Hazard designation:

Safety designation:

Hazardous components for labelling:

2. 3. Other Hazards

This product is capable of dust explosion under certain

circumstances.

According to regulation (EC) No. 1907/2006 (REACH)



# 26100 XSL Bismuth Vanadate Yellow

Page 2

3.

3. 1. Substance

3. 2. Mixture

Chemical Characterization: Bismuth vanadate pigment, water dispersable powder. Pigment

Yellow 184

Information on Components / Hazardous

Ingredients:

2-Butenedioic acid (2Z-)- polymer with 2-methyl-1-

propene and octadecene, sodium salt (H319)

1 - 3 % CAS-Nr: 191175-18-5

EINECS-Nr: EC-Nr:

Additional information:

4. First Aid Measures

4. 1. Description of the First Aid Measures

General information:

Remove contaminated clothes.

After inhalation:

Supply fresh air and seek medical advice in case of complaints.

After skin contact:

Remove contaminated clothing. Wash off immediately with plenty

of water and soap.

After eye contact:

Rinse open eyes with plenty of water for at least 15 minutes.

After ingestion:

Rinse mouth and give 200 - 300 ml of water to drink.

4. 2. Most important Symptoms and Effects, both Acute and Delayed

Symptoms:

No further information available.

Effects:

4. 3. Indication of any Immediate Medical Attention and special Treatment needed

Treatment:

Symptomatic treatment (decontamination, vital functions), no

specific antidote known.

5. Fire-Fighting Measures

5. 1. Extinguishing Media

Suitable extinguishing media:

Extingishing powder, foam.

Unsuitable extinguishing media:

Carbon dioxide (CO2)

5. 2. Special Hazards arising from the Substance or Mixture

Special hazards:

In case of fire: hazardous vapors may be released. Development3

According to regulation (EC) No. 1907/2006 (REACH)



#### 26100 XSL Bismuth Vanadate Yellow

Page 3

Revised edition: 27.10.2021 Version: 5.0 Printed: 18.02.2022

of fumes/aerosol.

5. 3. Advice for Firefighters

Protective equipment:

Wear self-contained respiratory protective device.

Further information:

Avoid formation of dust: risk of dust explosion.

#### 6. Accidential Release Measures

#### 6. 1. Personal Precautions, Protective Equipment and Emergency Procedures

Personal precautions:

Avoid formation of dust, wear protective clothing.

6. 2. Environmental Precautions

Environmental precautions:

Keep spills and cleaning runoff out of municipal sewers and open

bodies of water.

6. 3. Methods and Material for Containment and Cleaning Up

Methods and material:

Small spills:

Clean up with suitable appliance and dispose adequately.

Large spills:

Contain with dust binding material and dispose accordingly.

Avoid dust formation.

6. 4. Reference to other Sections

Protective clothing, see Section 8.

Dispose of contaminated material according to Section 13.

#### 7. Handling and Storage

# 7. 1. Precautions for Safe Handling

Instructions on safe handling:

Respiratory protection when handling without exhaust system.

Hygienic measures:

Do not inhale dust. Wash hands before breaks and at the end of

work.

7. 2. Conditions for Safe Storage, including any Incompatibilities

Storage conditions:

Store in tightly sealed containers in a dry and cool room.

Requirements for storage areas and

containers:

Keep container tightly closed.

Information on fire and explosion

protection:

Avoid dust formation. Protect against electrostatic charging.

Storage class:

11; Combustible solids (TRGS 510)

According to regulation (EC) No. 1907/2006 (REACH)



#### 26100 XSL Bismuth Vanadate Yellow

Page 4

Revised edition: 27.10.2021 Version: 5.0 Printed: 18.02.2022

Further Information:

Storage temperature: < 50°C

7. 3. Specific End Use(s)

Further information:

No further information available.

#### 8. Exposure Controls/Personal Protection

#### 8. 1. Parameters to be Controlled

Parameters to be controlled (DE):

**TRGS 900** 

Bismuth-vanadium tetraoxide (CAS 14059-33-7), TLV: 0.001

mg/m3 (airborne fraction); 8 (II)

Parameters to be controlled:

Derived No-Effect Level (DNEL):

Predicted No-Effect Concentration

(PNEC):

Additional Information:

#### 8. 2. Exposure Controls

Technical protective measures:

Personal Protection

General protective measures:

The usual precautionary measures are to be adhered to when

handling chemicals.

Protective clothing recommended due to the coloring effects of the

product.

Respiratory protection:

Suitable respiratory protection for lower concentration or shortterm effect: particle filter with medium efficiency for solid and liquid

particles (e.g. EN 143 or 149, type P2 or FFP2).

Hand protection:

Protective gloves (EN 374)

The manufacturer's directions for use should be observed

because of the great diversity of types.

Protective glove material:

Recommended: Protective index 6, corresponding > 480 min. of

permeation time according to EN 374.

Nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), polyvinyl

chloride (0.7 mm).

Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material and dexterity. Always seek advice from glove suppliers.

Eye protection:

Safety glasses with protective shields (EN 166).

Body protection:

Protective clothing.

According to regulation (EC) No. 1907/2006 (REACH)



#### 26100 **XSL Bismuth Vanadate Yellow**

Page 5

Revised edition: 27.10.2021 Version: 5.0 Printed: 18.02.2022

Environmental precautions:

Prevent from getting into the soil, surface water and sewage

system.

yellow

9. **Physical and Chemical Properties** 

9.1. Information on Basic Physical and Chemical Properties

> Form: granules

> Odor: odorless

Odor threshold:

Color:

no information available

pH-Value: 7 - 10 (100 g/l)

Melting temperature:

not determined

Boiling temperature:

not determined

Flash point:

not available

Evaporation rate:

This product is a non-volatile solid.

Flammability (solid, gas):

not highly flammable

Upper explosion limit:

no information available

Lower explosion limit:

no information available

Vapor pressure:

not applicable

Vapor density:

This product is a non-volatile solid.

Density:

not available

Solubility in water: insoluble

Coefficient of variation (n-

Octanol/Water):

no information available

Auto-ignition temperature:

Product is not auto-ignitable (Test type: Spontaneous self-ignition

at room temperature)

202°C; Test type: Spontaneous self-ignition at elevated

temperature (Method: VDI 2263, Sheet 1, 1.4.1)

Decomposition temperature:

LD50, oral:

According to regulation (EC) No. 1907/2006 (REACH)



#### 26100 XSL Bismuth Vanadate Yellow

Page 6 Revised edition: 27.10.2021 Version: 5.0 Printed: 18.02.2022 not determined Viscosity, dynamic: not applicable Explosive properties: Product does not present an explosion hazard. Oxidizing properties: not oxidizing Bulk density: 800 kg/m3 9. 2. **Further Information** Solubility in solvents: Viscosity, kinematic: Burning class: Solvent content: Solid content: Particle size: Other information: Hygroscopy: not hygroscopic 10. Stability and Reactivity 10.1. Reactivity Stable if used according to specifications. 10.2. **Chemical Stability** Stable if used according to specifications. 10.3. **Possibility of Hazardous Reactions** The product may contain explosive fine dust or such dust may be produced by abrasion during transport or product transfer. 10.4. **Conditions to Avoid** Conditions to avoid: Avoid formation of dust. Thermal decomposition: 10.5. **Imcompatible Materials** None known. 10.6. **Hazardous Decomposition Products** None if stored and handled according to specifications. 10.7. **Further Information** 11. **Toxicological Information** 11.1. Information on Toxicological Effects Acute Toxicity Practically not toxic after a single oral exposure.

> 5000 mg/kg (ATE)

According to regulation (EC) No. 1907/2006 (REACH)



# 26100 XSL Bismuth Vanadate Yellow

Page 7

Revised edition: 27.10.2021 Version: 5.0 Printed: 18.02.2022

LD50, dermal: > 5000 mg/kg (ATE)

LC50, inhalation:

not determined

Primary effects

Irritant effect on skin:

Slight irritant effect (rabbit; OECD 404)

Irritant effect on eyes:

Non-irritating to eyes (rabbit; OECD 405)

Inhalation:

No information available.

Ingestion:

No information available

Sensitization:

No sensitizing effects known (guinea pig; OECD 406).

Mutagenicity:

No mutagenic effects known.

Reproductive toxicity:

No relevant data found.

Carcinogenicity:

No relevant data found.

Teratogenicity:

No information available.

Specific target organ toxicity (STOT):

Single exposure: the substance or mixture is not classified as

specific target organ toxicant.

Repeated exposure: no information available.

Additional toxicological information:

Aspiration hazard: not applicable

# 12. Ecological Information

12. 1. Aquatic Toxicity

Not hazardous for aqueous organisms.

The product has not been tested. The statement has been derived

from the properties of the individual components.

Fish toxicity:

LC50: 10 - 100 mg/l (96 h, Danio rerio)

Daphnia toxicity:

not determined

Bacteria toxicity:

EC50: > 100 mg/l (Pseudomonas putida)

Algae toxicity:

not determined

According to regulation (EC) No. 1907/2006 (REACH)



#### 26100 XSL Bismuth Vanadate Yellow

Page 8

Revised edition: 27.10.2021 Version: 5.0 Printed: 18.02.2022

12. 2. Persistency and Degradability

Not readily biodegradable.

12. 3. Bioaccumulation

No bioaccumulation expected.

12. 4. Mobility

No accumulation by the organisms.

Does not evaporate from the surface of the water to the

atmosphere.

12. 5. Results of PBT- und vPvP Assessment

According to Annex VIII to Regulation (EC) No. 1907/2006

(REACH): this product is neither a PBT

(persistent/bioaccumulative/toxic) or vPvB (very persistent/very bioaccumulative/very toxic) substance nor does it contain a PBT or

vPvB substance.

12. 6. Other Adverse Effects

Water hazard class:

1, slightly hazardous

Behaviour in sewage systems:

No impairment of the biodegradability of active sludge expected when small amounts are discharged in biological sewage plants. Treatment in bological waste treatment plant has to be performed

according to local and administrative regulations.

Further ecological effects:

Do not discharge product uncontrolled into the environment. The data refer to the properties of the individual components.

AOX Value:

#### 13. Disposal Considerations

# 13. 1. Waste Treatment Methods

Product:

In accordance with current regulations, product may be taken to a

waste disposal site or incineration plant, after consultation with site

operator and/or with the responsible authority.

European Waste Code (EWC):

Uncleaned packaging:

Non contaminated packaging can either be recycled or utilized for

energy (incineration).

Contaminated packaging must be disposed like the substance.

Waste Code No.:

#### 14. Transport Information

#### 14. 1. UN Number

ADR. IMDG. IATA

#### 14. 2. UN Proper Shipping Name

ADR/RID:

According to regulation (EC) No. 1907/2006 (REACH)



#### 26100 **XSL Bismuth Vanadate Yellow**

raye	9

 $\sim$ 

Dago Revised edition: 27.10.2021 Version: 5.0 Printed: 18.02.2022 transportation). IMDG/IATA: Not hazardous goods 14. 3. **Transport Hazard Classes** ADR Class: not applicable Hazard no.: Classification code: Tunnel restriction code: IMDG Class (sea): not applicable Hazard no.: EmS No.: IATA Class: not applicable Hazard no.: 14. 4. **Packaging Group** ADR/RID: not applicable IMDG: IATA: 14. 5. **Environmental Hazards** None 14. 6. **Special Precautions for User** Not classified as a dangerous good under transport regulations. 14. 7. Transportation in Bulk according to Annex II of MARPOL 73/78 and IBC-Code not applicable 14. 8. **Further Information** 15. **Regulatory Information** 

#### 15. 1. Safety, Health and Environmental Regulations/Legislation specific for the Substance or Mixture

Water hazard class:

1, slightly hazardous for water (according to the German

Regulation AwSV)

Local regulations on chemical accidents:

Not listed.

Employment restrictions:

Restriction and prohibition of application:

Technical instructions on air quality:

According to regulation (EC) No. 1907/2006 (REACH)



# 26100 XSL Bismuth Vanadate Yellow

16.	Other Information			
		Regulation (EC) 2037/2000 - Substances that Deplete the Ozo Layer: not regulated / not applicable		the Ozone
15. 3.	Further Information			
		A Chemical Safety Assessment is not necessary for this product.		
15. 2.	Chemical Safety Assessment			
Revised edition: 27.10.2021		Version: 5.0	Printed:	18.02.2022
			Page	10

This product should be stored, handled and used in accordance with good hygiene practices and in conformity with any legal regulations. This information contained herein is based on the present state of knowledge and is intended to describe our product from the point of view of safety requirements. It should be therefore not be construed as guaranteeing specific properties.